



4G/LTE Flexible Printed Antenna



Part Number: L-2FA6

99 x 22 x 0.2 mm
 RoHS/RoHS II Compliant

Features

- Operates in 698-2700 MHz
- Linear polarization
- Low VSWR
- FPC flexible or PCB material (Optional)
- Omni-directional pattern
- Cable Solder direct or IPEX

Applications

- Cellular
- Transportation
- Industrial wearable
- Smart city
- Smart agriculture
- Home automation

Electrical Specifications

Parameters	Min.	Typ.	Max.	Units	Notes
Frequency Range		698~960/1710~2690		MHz	
VSWR	1.1		1.7		
Polarization Model	Linear				
Impedance	50			Ω	
Gain		4.5		dBi	

Mechanical Characteristics

Parameters	Description
Connector	Cable Solder direct or IPEX
Cable Type	RF1.13
Mounting	Adhesive Mount
FPC Dimensions	99 x 22 x 0.2 mm

Environmental Characteristics

Parameters	Note
Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
ROHS Compliant	Yes
MSL Level	1




4G/LTE Flexible Printed Antenna



Part Number: L-2FA6

99 x 22 x 0.2 mm
RoHS/RoHS II Compliant

Dimensions



Product Image



Antenna parameters

Frequency (MHz)	Efficiency	Gain (dBi)
698	0.70	1.3
824	0.61	1.6
868	0.57	1
960	0.56	1.9
1710	0.68	3.1
1850	0.67	2.0
1990	0.81	3.9
2170	0.72	2.2
2690	0.55	4.4





4G/LTE Flexible Printed Antenna



Part Number: L-2FA6

99 x 22 x 0.2 mm
RoHS/RoHS II Compliant







4G/LTE Flexible Printed Antenna



Part Number: L-2FA6

99 x 22 x 0.2 mm
RoHS/RoHS II Compliant






4G/LTE Flexible Printed Antenna



Part Number: L-2FA6

99 x 22 x 0.2 mm
RoHS/RoHS II Compliant






4G/LTE Flexible Printed Antenna



Part Number: L-2FA6

99 x 22 x 0.2 mm
RoHS/RoHS II Compliant

Radiation Patterns






4G/LTE Flexible Printed Antenna




Part Number: L-2FA6

99 x 22 x 0.2 mm
RoHS/RoHS II Compliant

3D – Pattern



750 and 850 MHz Radiation pattern



940 and 1750 MHz Radiation pattern




4G/LTE Flexible Printed Antenna




Part Number: L-2FA6

99 x 22 x 0.2 mm
RoHS/RoHS II Compliant



1850 and 1950 MHz Radiation pattern



2100 and 2600 MHz Radiation pattern



MiotWireless

Miot Wireless Solutions Ltd

<http://www.miotsolutions.com>

Info@miotsolutions.com

4G/LTE Flexible Printed Antenna



Part Number: L-2FA6

99 x 22 x 0.2 mm

RoHS/RoHS II Compliant

Packaging

TBD

Caution:

- (1) Do not apply excess mechanical stress to the component body or terminations. Do not attempt to re-form or bend the components as this will cause damage to the component.
- (2) Do not expose the component to open flame.
- (3) This specification applies to the functionality of the component as a single unit. Please ensure the component is thoroughly evaluated in the application circuit.