



# FM101-GL-00 4G Module

Perfect Wireless Experience

V1.3

## FM101-GL 4G Module Technical Specifications

### Product Features

- LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B66, B71
- LTE TDD: B38, B39, B40, B41, B42, B43, B48 (CBRS)
- WCDMA: B1, B2, B4, B5, B6, B8, B19
- HPUE: B41
- Transmitting Power: LTE: 23/24dBm WCDMA: 23.5dBm
- Receiver Sensitivity: LTE: -98dBm ~ -101dBm WCDMA: -109.5dBm ~ -111dBm
- Integrated GPS, GLONASS, BeiDou, Galileo
- Assisted GNSS (A-GNSS)
- Built-in eSIM
- Body SAR
- Antenna Tuner
- Operating Voltage: 3.135V ~ 4.4V, Typical 3.3V
- Operation Temperature: -10 ~ 55°C
- Storage Temperature: -40 ~ +85°C
- Form Factor: M.2 Key-B
- Size: 30\*42\*2.3 mm

### Data

#### Downlink:

- LTE: 300Mbps
- DC-HSPA+: 42Mbps

#### Uplink:

- LTE: 50Mbps
- DC-HSPA+: 5.76Mbps

### Interface

- USIM: 3V/1.8V
- USB 2.0 & 3.0
- MIPI
- I2C

### Operating System

- Chrome OS, Windows, Linux

### Approval

- FCC, PTCRB, CE, GCF, IC, TELEC, JATE, SRRC, CCC, NAL, NCC, RCM
- RoHS, REACH, TSCA, HF
- AT&T, Verizon, T-Mobile, Vodafone, Telefonica, DTAG, Telstra, Optus, DoCoMo, KDDI, Softbank